LED FIXTURE

TL Series

TUROLIGHT®

Metal Battery Pack
TL-EMRM

Steel housing battery pack

2-year limited warranty

Operating temperature range
10˚C ~ +40˚C
15˚C ~ +35˚C (140W)

TL-EMRM/90W/12VDC/2

TL-EMRM/90W/12VDC/0

TL-EMRM/140W

TL-EMRM/95W

TL-EMRM/36W

Features & Benefits

- Steel housing, UL-94V-0 flame rating, fire-resistant
- Input Voltage: 120/277/347V
- With or without 2×2W 6500K heads
- 12V / 6V sealed lead-acid battery
- Damp location rated, IP Class: IP20, not intended for outdoor use
- Wall mounting, remote capable

Dimensional Drawing



Ordering Information **Example: TL-EMRM/90W/12VDC/0/120-347V**

Family Name	Fixture Type	Wattage	Load Voltage	LED Heads	Input Voltage
TL (Turolight)	EMRM (Emergency remote)	36W 90W 95W 140W	6VDC 12VDC	0 (Without heads) 2 (With 2 LED heads)	120/277/347V

Product Specification

Ordering Code	Model Number	Description	Wattage (W)	Input Voltage (V)	LED Heads	Mounting	Remote Capable	Damp Location	Dimensions L×W×H (LH) (inch)	Case QTY.
3465200	TL-EMRM/36W/6VDC/2/120-347V	C/w 2x2W heads 36W, 6VDC, 120/277/347V, 90 Min at Max. Load	36	120/277/347V	2	Wall	Yes	Yes	11.8″×5.5″×2.95″(3.55″)	10
3466200	TL-EMRM/90W/12VDC/0/120-347V	No heads 64W, 12VDC, 120/277/347V, 30 Min at Max. Load	64	120/277/347V	0	Wall	Yes	Yes	10.2″×9.1″×3.27″	3
3466201	TL-EMRM/90W/12VDC/2/120-347V	C/w 2x2W heads 60W, 12VDC, 120/277/347V, 30 Min at Max. Load	60	120/277/347V	2	Wall	Yes	Yes	10.2″×9.1″×3.27″(5″)	3
3466202	TL-EMRM/95W/12VDC/2/120-347V	C/w 2x2W heads 95W, 12VDC, 120/277/347V, 30 Min at Max. Load	95	120/277/347V	2	Wall	Yes	Yes	12.2″×7.87″×2.76″(3.55″)	5
3461220	TL-EMRM/140W/12VDC/2/120-347V	C/w 2x2W heads 140W, 12VDC, 120/277/347V, 30 Min at Max. Load	140	120/277/347V	2	Wall	Yes	Yes	13.5″×8.97″×4.21″(3.55″)	5

Tel: 905-479-7093
Toll Free: 1-888-425-7093
Email: customerservice@turolight.com
Website: www.turolight.com