


A19 LED Light Bulbs

PV-A19/S2



2-year limited warranty

Operating temperature range -40 °C ~ +40 °C



Features & Benefits

cETLus listed

High CRI (80+)

Dimmable*


Enclosed fixture application*

15,000 hrs average life

Damp location rated

*For applicable models, see product specification below

Dimensional Drawing



Ordering Information Example: PV-A19/S2/9W/30/D

Family Name	Lamp Type	Wattage	CCT	Dimmable
PV (Pure Vision)	A19/S2	8.5W 9W 15W	27 (2700K) 30 (3000K) 40 (4000K) 50 (5000K)	D (Dimmable) Blank (Non-dimmable)

Product Specification

Ordering Code	Model Number	Wattage (W)	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture Application	Damp Location	Dimmable	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1732225	PV-A19/S2/9W/30/D	9	E26	120	15,000	220°	800	3000	80	Yes	Yes	Yes	2.36	4.13	40
1732424	PV-A19/S2/9W/40/D	9	E26	120	15,000	220°	800	4000	80	Yes	Yes	Yes	2.36	4.13	40
1732116	PV-A19/S2/8.5W/27	8.5	E26	120	15,000	180°	760	2700	80	No	Yes	No	2.38	4.3	48
1732226	PV-A19/S2/8.5W/30	8.5	E26	120	15,000	180°	760	3000	80	No	Yes	No	2.38	4.3	48
1732425	PV-A19/S2/8.5W/40	8.5	E26	120	15,000	180°	760	4000	80	No	Yes	No	2.38	4.3	48
1732520	PV-A19/S2/8.5W/50	8.5	E26	120	15,000	180°	760	5000	80	No	Yes	No	2.38	4.3	48
1733402	PV-A19/S2/15W/40	15	E26	120	15,000	180°	1600	4000	80	Yes	Yes	No	2.38	4.3	48
1732521	PV-A19/S2/15W/50	15	E26	120	15,000	180°	1600	5000	80	Yes	Yes	No	2.38	4.3	48