

# LED LAMP

## ARTISAN Series



## LED A15, A19, B10

Low Non Visible Flicker



2-year limited warranty

Operating temperature range -20 °C ~ +40 °C



### Features & Benefits

Reduced flicker down to 10%\*

- Compare to 6.6% traditional incandescent
- Far below California T20 standard 30%
- Significantly improve light quality
- Optimize eye comfort


With clear, amber or milky white glass cover

15,000 hour life (L70), high CRI (80+), dimmable

Damp location rated

\*Except AR-A19LF/8W & AR-A19LNVF/8W

### Dimensional Drawing



### Ordering Information Example: AR-A15LF/5W/30/D/C

| Family Name  | Lamp Type                                                                                          | Wattage  | CCT                                                  | Dimmable     | Cover                                      |
|--------------|----------------------------------------------------------------------------------------------------|----------|------------------------------------------------------|--------------|--------------------------------------------|
| AR (Artisan) | A15LF (A15, Low flicker)<br>A19LNVF/ A19LF (A19, Low flicker)<br>B10LNVF/ B10LF (B10, Low flicker) | 5W<br>8W | 22 (2200K)<br>27 (2700K)<br>30 (3000K)<br>40 (4000K) | D (Dimmable) | C (Clear)<br>A (Amber)<br>MW (Milky white) |

### Product Specification

| Ordering Code | Energy Star | Model Number              | Product Description                                      | Watts (W) | Replacement Filament | Replacement Incandescent | Base | Voltage (V) | Hour Rating | Beam Angle | Initial Lumens (lm) | CCT(K) | CRI | Damp Loc. | M.O.L. (inch) | Case QTY. |
|---------------|-------------|---------------------------|----------------------------------------------------------|-----------|----------------------|--------------------------|------|-------------|-------------|------------|---------------------|--------|-----|-----------|---------------|-----------|
| 1771209       | -           | AR-A15LF/5W/30/D/C        | A15 Low Flicker 5W 30K Dimmable Clear                    | 5         | -                    | 40W                      | E26  | 120         | 15,000      | 330°       | 500                 | 3000   | 80  | Y         | 3.54          | 40        |
| 1771213       | -           | AR-A15LF/5W/30/D/MW       | A15 Low Flicker 5W 30K Dimmable Milky white              | 5         | -                    | 40W                      | E26  | 120         | 15,000      | 330°       | 450                 | 3000   | 80  | Y         | 3.54          | 40        |
| 1771210       | -           | AR-A15LF/5W/30/D/F        | A15 Low Flicker 5W 30K Dimmable Milky white              | 5         | -                    | 40W                      | E26  | 120         | 15,000      | 330°       | 450                 | 3000   | 80  | Y         | 3.54          | 40        |
| 1772110       | -           | AR-A19LF/8W/27/D/C        | A19 Low Flicker 8W 27K Dimmable Clear                    | 8         | -                    | 60W                      | E26  | 120         | 15,000      | 330°       | 800                 | 2700   | 80  | Y         | 4.29          | 40        |
| 1772202       | -           | AR-A19LF/8W/30/D/C        | A19 Low Flicker 8W 30K Dimmable Clear                    | 8         | -                    | 60W                      | E26  | 120         | 15,000      | 330°       | 800                 | 3000   | 80  | Y         | 4.29          | 40        |
| 1772205       | -           | AR-A19LF/8W/30/D/MW       | A19 Low Flicker 8W 30K Dimmable Milky white              | 8         | -                    | 60W                      | E26  | 120         | 15,000      | 330°       | 750                 | 3000   | 80  | Y         | 4.29          | 40        |
| 1772115       | -           | AR-A19LNVF/8W/27/D/C      | A19 Low Flicker New Generation 8W 27K Dimmable Clear     | 8         | -                    | 60W                      | E26  | 120         | 15,000      | 330°       | 800                 | 2700   | 80  | Y         | 4.29          | 20        |
| 1772207       | -           | AR-A19LNVF/8W/30/D/C      | A19 Low Flicker New Generation 8W 30K Dimmable Clear     | 8         | -                    | 60W                      | E26  | 120         | 15,000      | 330°       | 800                 | 3000   | 80  | Y         | 4.29          | 20        |
| 1771149       | -           | AR-B10LNVF/5W/27/E12/D/C  | B10 Low Flicker New Generation 5W 27K E12 Dimmable Clear | 5         | -                    | 60W                      | E12  | 120         | 15,000      | 330°       | 500                 | 2700   | 80  | Y         | 3.78          | 50        |
| 1771223       | -           | AR-B10LNVF/5W/30/E12/D/C  | B10 Low Flicker New Generation 5W 30K E12 Dimmable Clear | 5         | -                    | 60W                      | E12  | 120         | 15,000      | 330°       | 500                 | 3000   | 80  | Y         | 3.78          | 50        |
| 1771229       | Yes         | AR-B10LF/5W/30/E12/D/C/ES | B10 Low Flicker 5W 30K E12 Dimmable Clear Energy Star    | 5         | -                    | 60W                      | E12  | 120         | 15,000      | 330°       | 500                 | 3000   | 80  | Y         | 3.78          | 96        |
| 1771222       | -           | AR-B10LF/5W/30/E12/D/MW   | B10 Low Flicker 5W 30K E12 Dimmable Milky white          | 5         | -                    | 60W                      | E12  | 120         | 15,000      | 330°       | 450                 | 3000   | 80  | Y         | 3.78          | 50        |
| 1771406       | -           | AR-B10LNVF/5W/40/E12/D/C  | B10 Low Flicker New Generation 5W 40K E12 Dimmable Clear | 5         | -                    | 60W                      | E12  | 120         | 15,000      | 330°       | 500                 | 4000   | 80  | Y         | 3.78          | 50        |
| 1771930       | -           | AR-B10LNVF/5W/22/E12/D/A  | B10 Low Flicker New Generation 5W 22K E12 Dimmable Amber | 5         | 60W                  | -                        | E12  | 120         | 15,000      | 330°       | 450                 | 2200   | 80  | Y         | 3.78          | 50        |
| 1771150       | -           | AR-B10LNVF/5W/27/D/C      | B10 Low Flicker New Generation 5W 27K E26 Dimmable Clear | 5         | -                    | 60W                      | E26  | 120         | 15,000      | 330°       | 500                 | 2700   | 80  | Y         | 3.78          | 50        |



Tel: 905-479-7093  
Toll Free: 1-888-425-7093

Email: sales@turolight.com  
Website: www.turolight.com